



ARTISTRY - MH Series Indoor LED is a **dynamic, high definition** LED display allowing **boundless opportunities** to create an unforgettable space. Each frame is manufactured specifically for your installation. This series includes 1.25mm, 1.667mm, 1.875mm and 1.923mm which provide **sharp image output, fluent video displaying** and **high refresh rate**. The special design for **front and rear access** saves time and labor in display maintenance. Also, the premium materials used in LED display enhance the reliability of the display which guarantees you the **long life-span** and steady performance.

#### Application

- Hotel
- Stage rental
- TV
- Large market
- Playground

#### · High Colour Fidelity



#### · Wide Viewing Angle



#### · Ultra High-resolution Pitches



#### · Multi Pixel Pitches For Options



# ARTISTRY - MH Series Indoor LED

Model	P1.25	P1.667	P1.875	P1.923
<b>Optical Parameter</b>				
Pixel Pitch (mm)	1.25	1.667	1.875	1.923
Pixel Configuration	1R1G1B (3 in 1)	1R1G1B (3 in 1)	1R1G1B (3 in 1)	1R1G1B (3 in 1)
Pixel Density (Pixel/m <sup>2</sup> )	640000	360000	284440	270400
Viewing Angle (H/V)	160° / 160°	160° / 160°	160° / 160°	160° / 160°
Brightness (cd/m <sup>2</sup> )	300-800	800	800	800
Contrast Ratio	≥3000 : 1	≥3000 : 1	≥3000 : 1	≥3000 : 1
Color Temperature	6500-12000K	7500-8500K	7500-8500K	7500-8500K
Processing Depth	>14bit	>14bit	≥14bit	≥14bit
Refresh Rate	≥2400Hz	≥2880Hz	≥2880Hz	≥2880Hz
Optimized Viewing Distance (m)	1.3	1.7	1.875	2
<b>Structure Parameter</b>				
Cabinet Size in Pixel (W × H)	384 × 216	240 × 180	256 × 256	208 × 156
Cabinet Size in mm (W × H × D)	480 × 270 × 50	400 × 300 × 75	480 × 480 × 75	400 × 300 × 75
Cabinet Weight (kg/m <sup>2</sup> )	37	40	36	40
IP Rating	IP30	IP30	IP43	IP30
<b>Operation Parameter</b>				
Maintenance	Front/Rear Access			
Operating Temperature	-20C~60C			
Operating Humidity	10~90 RH%			
Life Time (50% Brightness)	>50,000 Hours			
Power Consumption (Max.)	50-100W per sqm	100W per sqm	140W per sqm	100W per sqm
Power Consumption (Min.)	10-35W per sqm	35W per sqm	45W per sqm	35W per sqm
<b>System Parameter</b>				
Video Signal Input	HDMI / DVI-D			



ARTISTRY - MH系列室内LED是一种动态的高清LED显示屏，为您创造难忘的显示空间。每个框架都能按客户的安装需求度身订造。MH系列包括1.25mm、1.667mm、1.875mm和1.923mm，提供清晰的图像输出、流畅的视频显示和高刷新率。另外，此系列支持前及后维护，节省显示器维护的时间和人力。ARTISTRY - MH系列室内LED使用优质材料以增强显示器的可靠性，保证LED运作較长的寿命和提供稳定的性能。

#### 应用

- 酒店
- 舞台租赁
- 电视
- 大型市场
- 游乐场

#### · 高色彩保真度



#### · 广宽的视角



#### · 超高分辨率



#### · 多项显示屏像素间距可选



型号	P1.25	P1.667	P1.875	P1.923
<b>光学参数</b>				
点间距 (mm)	1.25	1.667	1.875	1.923
发光管类型	1R1G1B (3 in 1)	1R1G1B (3 in 1)	1R1G1B (3 in 1)	1R1G1B (3 in 1)
点密度 (点/m <sup>2</sup> )	640000	360000	284440	270400
视角 (水平/垂直)	160° / 160°	160° / 160°	160° / 160°	160° / 160°
亮度 (cd/m <sup>2</sup> )	300-800	800	800	800
对比度	≥3000 : 1	≥3000 : 1	≥3000 : 1	≥3000 : 1
色温	6500-12000K	7500-8500K	7500-8500K	7500-8500K
处理深度	>14bit	>14bit	≥14bit	≥14bit
刷新率 (Hz)	≥2400Hz	≥2880Hz	≥2880Hz	≥2880Hz
最佳观看距离 (m)	1.3	1.7	1.875	2
<b>结构参数</b>				
模组尺寸 (W×H)/点	384 × 216	240 × 180	256 × 256	208 × 156
模组尺寸 (W×H×D)/mm	480 × 270 × 50	400 × 300 × 75	480 × 480 × 75	400 × 300 × 75
模组重量 (kg/m <sup>2</sup> )	37	40	36	40
防护等级	IP30	IP30	IP43	IP30
<b>操作参数</b>				
维护方式	前/后			
工作温度	-20℃~60℃			
工作湿度	10~90 RH%			
寿命 (亮度为50% 时)	>50,000 小时			
最大功耗 (W/m <sup>2</sup> )	50-100W	100W	140W	100W
平均功耗 (W/m <sup>2</sup> )	10-35W	35W	45W	35W
<b>系统参数</b>				
视频信号输入	HDMI / DVI-D			