



ARTISTRY - YS2 Series Indoor LED is the product designed for indoor applications with the indoor surface mounted diode. With our unique calibration technology, calibration on every pixel can be perfectly executed to make sure the high brightness and color homogeneity. ARTISTRY YS2 Series Indoor LED is our first indoor product applied in the A-list brands like Louis Vuitton since 2005. After years of improvement, its stability has already been proved.

**Application**

- Retail Store
- Shopping Mall
- Airport
- Bank Center
- Security & Finance
- Conference Hall
- Theater
- Shopping Mall

· Solidly-built architecture



· Full sets of certificates available



· 24/7 smart monitoring service



· High contrast



# ARTISTRY - YS2 Series Indoor LED

Model	P4	P6	P8	P10	P12
<b>Optical Parameter</b>					
Pixel Pitch (mm)	4	6	8	10	12
Pixel Configuration	3 in 1 SMD	3 in 1 SMD	3 in 1 SMD	3 in 1 SMD	3 in 1 SMD
Pixel Density (Pixel/m <sup>2</sup> )	62500	27777	15625	10000	6944
Viewing Angle (H/V)	140° / 140°	140° / 140°	140° / 140°	140° / 140°	140° / 140°
Brightness (cd/m <sup>2</sup> )	600-1200	1500-3500	1500-3500	1500-3500	1500-3500
Contrast Ratio	≥4000 : 1	≥2000 : 1	≥2000 : 1	≥2000 : 1	≥2000 : 1
Color Temperature	5500-8000K	5500-8000K	5500-8000K	5500-8000K	5500-8000K
Processing Depth	16bit	16bit	16bit	16bit	16bit
Refresh Rate	≥1920Hz	≥1920Hz	≥1920Hz	≥1920Hz	≥1920Hz
Optimized Viewing Distance (m)	4	6	8	10	12
<b>Structure Parameter</b>					
Cabinet Size in Pixel (W × H)	128 × 128	128 × 128	128 × 128	128 × 64	64 × 64
Cabinet Size in mm (W × H × D)	512 × 512 × 135	768 × 768 × 135	1024 × 1024 × 135	1280 × 640 × 135	768 × 768 × 135
Cabinet Weight (kg/m <sup>2</sup> )	40	40	40	40	40
IP Rating	IP32	IP32	IP32	IP32	IP32
<b>Operation Parameter</b>					
Maintenance	Front/Rear Access				
Operating Temperature	-20°C~50°C				
Operating Humidity	10~90 RH%				
Life Time (50% Brightness)	≥100,000 Hours				
Power Consumption (Max.)	480W per sqm	400W per sqm	400W per sqm	400W per sqm	400W per sqm
Power Consumption (Avg.)	180W per sqm	160W per sqm	160W per sqm	160W per sqm	160W per sqm
<b>System Parameter</b>					
Video Signal Input	VGA / DVI-D				



ARTISTRY - YS2系列室内LED配置室内表面贴装二极管，专为室内应用而设。凭借我们独特的校准技术，可以完美地执行每个像素的校准，以确保高亮度和颜色的均匀性。我们自2005年以来不断应用ARTISTRY YS2系列室内LED于Louis Vuitton等A级品牌。经过多年的改进，其稳定性毋庸置疑。

应用

- 零售店
- 购物中心
- 机场
- 银行中心
- 安全中心与金融领域
- 会议厅
- 剧院
- 购物中心

· 结构坚固



· 提供全套证书



· 24/7 智能监控服务



· 高对比度



型号	P4	P6	P8	P10	P12
<b>光学参数</b>					
点间距 (mm)	4	6	8	10	12
发光管类型	3 in 1 SMD	3 in 1 SMD	3 in 1 SMD	3 in 1 SMD	3 in 1 SMD
点密度 (点/m <sup>2</sup> )	62500	27777	15625	10000	6944
视角 (水平/垂直)	140° / 140°	140° / 140°	140° / 140°	140° / 140°	140° / 140°
亮度 (cd/m <sup>2</sup> )	600-1200	1500-3500	1500-3500	1500-3500	1500-3500
对比度	≥4000 : 1	≥2000 : 1	≥2000 : 1	≥2000 : 1	≥2000 : 1
色温	5500-8000K	5500-8000K	5500-8000K	5500-8000K	5500-8000K
处理深度	16bit	16bit	16bit	16bit	16bit
刷新率 (Hz)	≥1920Hz	≥1920Hz	≥1920Hz	≥1920Hz	≥1920Hz
最佳观看距离 (m)	4	6	8	10	12
<b>结构参数</b>					
模组尺寸 (W×H)/点	128 × 128	128 × 128	128 × 128	128 × 64	64 × 64
模组尺寸 (W×H×D)/mm	512 × 512 × 135	768 × 768 × 135	1024 × 1024 × 135	1280 × 640 × 135	768 × 768 × 135
模组重量 (kg/m <sup>2</sup> )	40	40	40	40	40
防护等级	IP32	IP32	IP32	IP32	IP32
<b>操作参数</b>					
维护方式	前/后				
工作温度	-20℃~50℃				
工作湿度	10~90 RH%				
寿命 (亮度为50% 时)	≥100,000 小时				
最大功耗 (W/m <sup>2</sup> )	480W	400W	400W	400W	400W
平均功耗 (W/m <sup>2</sup> )	180W	160W	160W	160W	160W
<b>系统参数</b>					
视频信号输入	VGA / DVI-D				